


# CAST IRON ODP



ASHH, NEMA PREMIUM [DHP]\*

Effective 07-08-18  
Supersedes 03-24-17



## APPLICATIONS:

- Fans & Blowers
- Pumps
- Compressors
- HVAC Equipment
- Fire Pumps\*



## FEATURES:

- Output Range: 1 - 800 HP
- Speed: 3600, 1800 & 1200 RPM
- Enclosure: Open Drip Proof (IP22)
- Voltage: 230/460V (Usable on 208V); 150HP and Larger is 460V Only<sup>(1)</sup>
- Three Phase, 60 Hz, 1.15 Service Factor (Continuous); 50 Hz, 1.0 Service Factor (Continuous)
- Class F Insulation
- Class B Temperature Rise
- NEMA Design B Torques
- Cast Iron Frame and End Brackets
- Rolled Steel Main Conduit Box
- Grounding Terminal Inside Main Conduit Box
- Oversized Main Conduit Box Rotatable in 90 Degree Increments - F1 Mounted
- Designed for 40°C Ambient Temperature<sup>(2)</sup>
- Designed for 3300 ft. Elevation<sup>(3)</sup>
- Bi-Directional Rotation
- 1045 Carbon Steel Shaft
- Aluminum Die Cast Squirrel Cage Rotor Construction
- Paint System: Phenolic Rust Proof Base Plus Polyurethane Top Coat
- Paint Color: Light Gray - Munsell N5.0
- Double Shielded Bearings Pre-Packed with MULTEMP SRL for F# 140T - 280T (Non-regreasable)
- High Quality Ball (or Roller) Bearings regreasable with Mobil Polyrex™ EM for F# 280TS and Larger
- Labyrinth Type Metal Flinger on Both Ends for F# 280TS and Larger
- Cast Iron Inner and Outer Bearing Caps for F#280TS and Larger
- Stainless Steel Nameplate
- New Dual Column Design Nameplate as Standard (60/50 Hz)
- Suitable for Inverter Use per NEMA MG-1 Part 31.4.4.2<sup>(4,5)</sup>
- Inverter Duty Speed Range: 20:1 Variable Torque, 10:1 Constant Torque
- 9 Leads for 5 HP and Smaller;
- 12 Leads for 7.5 HP to 125 HP;
- 6 Leads for 150 HP and Larger
- Motors are U.L. Recognized, CSA Approved and CE Marked

## EXTRAS/ OPTIONS:

Please refer to pages 147 - 154 for common modifications that can be performed.

### Notes:

\* Fire Pump available. See product page for more details.

- (1) Available in 575V. TWMC carries minimal 575V stock; please check availability to ensure required motors are in stock.  
Ratings may be available from our Canadian warehouses and/or our factory. Pricing and leadtime may vary.
- (2) Consult a Stock Product Application Specialist for suitability in higher ambient environments.
- (3) Consult a Stock Product Application Specialist for suitability in higher elevations.
- (4) Motor service factor is 1.0 when operated on a VFD.
- (5) Precautions should be taken to eliminate or reduce shaft currents that may be imposed on the motor by the VFD as stated per NEMA MG-1, Part 31.